



### Technical Data

Handle length mm	Frame length mm	Min. height mm	Lifting height/ capacity mm/t	Lifting height/ capacity mm/t	Frame width mm	Frame width w. wheels mm	Standard extensions mm	Weight kg
A	B	C	D	E	G	H	I	
510	540	162	234/25	317/10	225	271	50/100	28

Extensions are not to exceed 250 mm.

### OPTIONS:



**Extension Handle**  
44 860 00 HF  
increases the reach  
by 450mm



**Extension**  
44 020 00 F250  
250mm



**Jack saddle**  
44 021 00 FW  
ø145mm  
max. capacity 10 tons



**V-saddle**  
63 231 00 FW1  
max. capacity 10 tons



**Transit locking device**  
44 870 00 SBB



## PORTABLE AIR-HYDRAULIC JACK

- Ideal for service trucks, tyre shops and road service

AC Hydraulic A/S  
Fanøvej 6 DK-8800 Viborg Tel. +45 86 62 21 66 Fax +45 86 62 29 88  
E-mail [ac@ac-hydraulic.dk](mailto:ac@ac-hydraulic.dk)

[www.ac-hydraulic.com](http://www.ac-hydraulic.com)



AC Hydraulic A/S

# Portable air-hydraulic jack Model B25-2

## Ideal for service trucks, tyre shops and road service

- Ultra low weight and a lifting capacity of 25 ton
- All functions are operated from one handle
- Optimum safety - dead man's control, safety valve and transit locking device



In spite of its ultra low weight the portable air-hydraulic jack (B25-2) has a lifting capacity of 25 ton!

The design is unique with integrated tubes and valves. All functions are operated from one handle which combines carrying, steering and operation (lifting/lowering).

Manually operated dead man's release ensures safe lowering and the built-in safety valve prevents overloading.

The jack can be supplied with a handy and practical transit locking device for safe storage to avoid damages caused by short stop.

B25-2 is a quality product with among other things long life hard chrome plated piston rods. The portable air-hydraulic jack is therefore designed for commercial use in both workshops and service trucks.

Supplied with two extensions of 50/100 mm.

**2 years warranty**



Trucks/Busses  
Model 25-1

Trucks/Busses  
Model 25-2

Trucks/Busses  
Model 50-2

Trucks/Busses  
Model 50-3H

Busses w. low clearance  
Model 50-3

Agriculture/Contractors  
Model 25-1H

Trucks/Contractors  
Model 65-1

Trucks/Contractors  
Model 65-1H

**Capacity:**  
25t  
**Min. height:**  
220mm  
**Max. height:**  
345mm



**Capacity:**  
25t / 10t  
**Min. height:**  
180mm  
**Max. height:**  
272mm (25 t)  
375mm (10 t)



**Capacity:**  
50t / 25t  
**Min. height:**  
220mm  
**Max. height:**  
337mm (50 t)  
445mm (25 t)



**Capacity:**  
50t / 25 t / 10t  
**Min. height:**  
220mm  
**Max. height:**  
337mm (50 t)  
445mm (25 t)  
558mm (10 t)



**Capacity:**  
50t / 25 t / 10t  
**Min. height:**  
150mm  
**Max. height:**  
210mm (50 t)  
263mm (25 t)  
332mm (10 t)



**Capacity:**  
25t  
**Min. height:**  
360mm  
**Max. height:**  
610mm



**Capacity:**  
65t  
**Min. height:**  
245mm  
**Max. height:**  
382mm



**Capacity:**  
65t  
**Min. height:**  
430mm  
**Max. height:**  
730mm

